

ECOSLIP 100

Drum Slip Agent/Anti Knotting Agent

Chemical composition	Blend of Organic and Inorganic compounds
Appearance	Dull White powder
Solubility	Sparingly soluble in water
Shelf life	Up to 1 year at temperatures between 5 and 40° C.
Dilution	Added Undiluted

Field of application:

For reducing the friction and tie-up/knotting between leathers

Properties:

- » ECOSLIP 100 will reduce the friction between the leather in the drum during wet process thereby avoiding the heat.
- » ECOSLIP will smoothen the water lightly syrupy and hence the leathers will not tie up and hence knotting of leathers is avoided which results in leathers without damage.
- » Does not react with the leather or the chemicals used in the process and hence there will be no adverse effect to the tanning process

Usage Quantity:

Depending upon end load of drum 0.1% to 0.5% will be enough

Note: The product being combination of various raw materials, there are chances of variations in colour and viscosity. The property and application of the product will remain same.

Store within 5°C to 35°C in original pack with tightly closed.

The above information on application on leather is given in accordance to the best of our knowledge and our lab applications. As the usage of the product by the consumer is not under our control, we are not liable for any sort of claims or reimbursements. The product is given without any guarantee/warranty in connection to end use.

ZSIVIRA CHEMIE MERK PRIVATE UMITED