



ZSIVILAC MS02

Lacquer Emulsion

Chemical composition	Nitrocellulose with Solvents and Emulsifiers
Solids	Approx 17%
Appearance	White Emulsion
Film	Medium Glossy, Soft, Stretchy
Shelf life	Up to 6 months at temperatures between 5 and 40° C.

Properties and Application

ZSIVILAC MS02 is a medium shine emulsion lacquer based on Nitrocellulose.

ZSIVILAC MS02 is used as top coat to give clear, Medium glossy, stretchy film.

ZSIVILAC MS02 does not probate grain harshness.

ZSIVILAC MS02 with stands both very high and very low temperatures.

ZSIVILAC MS02 does not cause blushing even in temperatures below zero degrees due to high grade raw materials used.

ZSIVILAC MS02 withstands milling for long hours without film break.

ZSIVILAC MS02 is normally used in dilution ration of 1:1 with water.

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale and Delivery.

ZSIVIRA CHEMIE MERK PRIVATE LIMITED

01/10