



# ZSIVILAC SM 964

Butter Lacquer Emulsion

<b>Chemical composition</b>	Nitrocellulose with Solvents and Emulsifiers and feel modifiers
<b>Solids</b>	Approx 18%
<b>Appearance</b>	White Emulsion
<b>Film</b>	Medium Glossy, Soft, Stretchy, waxy
<b>Shelf life</b>	Up to 6 months at temperatures between 5 and 40° C.

## Properties and Application

ZSIVILAC SM964 produces medium shine to dull film on the leather.

ZSIVILAC SM964 is used as top coat for drum dyed articles where slippery touch with very little shine is needed.

ZSIVILAC SM964 withstands tape test.

ZSIVILAC SM964 is normally used in dilution ration of 1:1 with water.

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale and Delivery.

**ZSVIRA CHEMIE MERK PRIVATE LIMITED**

01/10