

REZINE MS76

Chemical compositionProprietary acrylic Polymer blendAppearanceMilky EmulsionSolidsApprox 30%pH 10%7.0 - 8.5%ChargeAnionicFilmMedium Soft, Tough & Low TackShelf Life6 months from the date of manufacture

Properties:

- » REZINE MS76 provides high covering in base coat.
- » It with stands high pressure and high temperature plating / embossing.
- » Outstanding Wet and Dry Rub Fastness.
- » Excellent print retention for Printed Dry Milled articles.
- » Can be used in Base Coats, intermediate coats in finishing of shoe softy, uppers, garments, gloves and milled articles.
- » Excellent light fastness and hence suitable for wet white and pastel colour finishes.

Usage:

Recommended 100 to 250 Parts in base coats and intermediate coats.

Note : The product being combination of various raw materials, there are chances of variations in colour and viscosity. The property and application of the product will remain same. Store within 5°C to 35°C in original pack with tightly closed.

The above information on application on leather is given in accordance to the best of our knowledge and our lab applications. As the usage of the product by the consumer is not under our control, we are not liable for any sort of claims or reimbursements. The product is given without any guarantee/warranty in connection to end use.

ZSIVIRA CHEMIE MERK PRIVATE LIMITED

www.zsiviraindia.com | info@zsiviraindia.com